

# Package: R2Addhaz (via r-universe)

September 13, 2024

**Type** Package

**Title** R2 Measure of Explained Variation under the Additive Hazards Model

**Version** 0.1.0

**Date** 2020-03-20

**Author** Denise Rava

**Maintainer** Denise Rava <drava@ucsd.edu>

**Description**  $R^2$  measure of explained variation under the semiparametric additive hazards model is estimated. The measure can be used as a measure of predictive capability and therefore it can be adopted in model selection process. Rava, D. and Xu, R. (2020) <[arXiv:2003.09460](https://arxiv.org/abs/2003.09460)>.

**License** GPL-2

**Encoding** UTF-8

**LazyData** true

**RdMacros** Rdpack

**Imports** ahaz, pracma, zoo, caTools, survival, Rdpack (>= 0.7)

**NeedsCompilation** no

**Date/Publication** 2020-04-07 15:20:02 UTC

**Repository** <https://deniserava.r-universe.dev>

**RemoteUrl** <https://github.com/cran/R2Addhaz>

**RemoteRef** HEAD

**RemoteSha** 50f00a386a79dc299f499c698abe9168e8d7401c

## Contents

R2addhaz . . . . .	2
<b>Index</b>	<b>3</b>

---

`R2addhaz`*Estimate R<sup>2</sup> for additive hazards model*

---

**Description**

The function computes R<sup>2</sup> measure of explained variation under the semiparametric additive hazards model.

**Usage**

```
R2addhaz(data)
```

**Arguments**

`data` a data.frame with survival data. The first column needs to be the censored failure time. The second column needs to be the event indicator, 1 if the event is observed, 0 if it is censored. The other columns are covariates.

**Details**

The semiparametric hazards model

$$\lambda(t|Z) = \lambda_0(t) + \beta Z$$

is fitted to the data. The R<sup>2</sup> measure of explained variation is then computed.

**Value**

R R<sup>2</sup> measure of explained variation.

**Author(s)**

Denise Rava

**References**

Rava, D., Xu, R. "Explained Variation under the Additive Hazards Model", March 2020, arXiv:2003.09460

**Examples**

```
Z=runif(100,0,sqrt(3)) #generate covariates
u=runif(100,0,1)
t=-log(u)/as.vector((1+Z)) #generate failure time
status=rep(1,100) #censoring indicator
sd<-as.data.frame(cbind(t,status,Z)) #data frame of survival data
R2addhaz(sd)
```

# Index

\* **~AdditiveHazardsModel**

R2addhaz, [2](#)

\* **~R2**

R2addhaz, [2](#)

R2addhaz, [2](#)